

IN THE CLAIMS:

The following is a complete listing of claims in this application.

Claims 1-58 (canceled).

59. (currently amended) A device for cleaning dogs comprising a basin having a bottom and a side wall extending upwards from this bottom and comprising a perforated intermediate bottom arranged inside the space enclosed by the basin at a vertical distance from the basin edge, wherein underneath the intermediate bottom there is arranged a first branch of an air supply system connected to a controllable blower which is provided with air outlet openings distributed uniformly over the base surface, which are directed laterally and/or downwards,

wherein a manually guidable water hose is provided which can be supplied with rinsing water from the cleaning water located in the device via a dirt filter and a feed pump which can be switched on and off.

60. (previously presented) The device according to claim 59, wherein the air supply system comprises channels running in a horizontal plane with air outlet openings opening to both sides.

Claim 61 (canceled).

62. (currently amended) A device for cleaning dogs comprising a basin having a bottom and a side wall extending upwards from this bottom and comprising a perforated intermediate bottom arranged inside the space enclosed by the basin at a vertical distance from the basin edge, wherein underneath the intermediate bottom there is arranged a first branch of an air supply system connected to a controllable blower which is provided with air outlet openings distributed uniformly over the base surface, which are directed laterally

and/or downwards,

~~The device according to claim 59,~~ wherein a heating device for heating the conveyed air is incorporated after the blower.

63. (currently amended) A device for cleaning dogs comprising a basin having a bottom and a side wall extending upwards from this bottom and comprising a perforated intermediate bottom arranged inside the space enclosed by the basin at a vertical distance from the basin edge, wherein underneath the intermediate bottom there is arranged a first branch of an air supply system connected to a controllable blower which is provided with air outlet openings distributed uniformly over the base surface, which are directed laterally and/or downwards,

~~The device according to claim 59,~~ wherein connected to the blower is a second branch of the air supply system which can be switched on and off separately, which has obliquely downwardly directed second air outlet openings arranged in the upper region of the inside of the side wall of the basin, wherein the section of the second branch of the air supply system having the second air outlet openings is arranged such that it is adjustable in height.

64. (previously presented) The device according to claim 63, wherein the second branch has a manually guidable air hose which can be acted upon with air as desired.

65. (currently amended) A device for cleaning dogs comprising a basin having a bottom and a side wall extending upwards from this bottom and comprising a perforated intermediate bottom arranged inside the space enclosed by the basin at a vertical distance from the basin edge, wherein underneath the intermediate bottom there is arranged a first branch of an air supply system connected to a controllable

blower which is provided with air outlet openings distributed uniformly over the base surface, which are directed laterally and/or downwards,

~~The device according to claim 59,~~ wherein a metering device to deliver an additive into the air flow is connected to the first branch of the air supply system.

66. (currently amended) A device for cleaning dogs comprising a basin having a bottom and a side wall extending upwards from this bottom and comprising a perforated intermediate bottom arranged inside the space enclosed by the basin at a vertical distance from the basin edge, wherein underneath the intermediate bottom there is arranged a first branch of an air supply system connected to a controllable blower which is provided with air outlet openings distributed uniformly over the base surface, which are directed laterally and/or downwards,

~~The device according to claim 59,~~ wherein the intermediate bottom is assigned a lifting device which is suitable for lifting the intermediate bottom from its base position associated with a cleaning phase into a position associated with a drying phase and keeping it there for a while.

67. (currently amended) A device for cleaning dogs comprising a basin having a bottom and a side wall extending upwards from this bottom and comprising a perforated intermediate bottom arranged inside the space enclosed by the basin at a vertical distance from the basin edge, wherein underneath the intermediate bottom there is arranged a first branch of an air supply system connected to a controllable blower which is provided with air outlet openings distributed uniformly over the base surface, which are directed laterally and/or downwards,

~~The device according to claim 59, wherein it is provided with additionally comprising a level sensor which is suitable constructed and arranged~~ for emitting a first signal when an adjustable maximum filling height is reached in the basin and emitting a second signal after leaving this maximum filling height as soon as the emptied state of the basin is reached, wherein for signal transmission the level sensor is connected to a control circuit which is suitable for controlling at least the blower, ~~possibly~~ and optionally the heating, the duration of the cleaning and drying phase and ~~possibly~~ the function of the feed pump for filling or emptying the basin according to signals obtained from the level sensor and from an adjustable time switch member.

68. (currently amended) A device for cleaning dogs comprising a basin having a bottom and a side wall extending upwards from this bottom and comprising a perforated intermediate bottom arranged inside the space enclosed by the basin at a vertical distance from the basin edge, wherein underneath the intermediate bottom there is arranged a first branch of an air supply system connected to a controllable blower which is provided with air outlet openings distributed uniformly over the base surface, which are directed laterally and/or downwards,

~~The device according to claim 59, wherein the first branch of the air supply system is connected to the intermediate bottom at a distance from its underside.~~

69. (currently amended) A device for cleaning dogs comprising a basin having a bottom and a side wall extending upwards from this bottom and comprising a perforated intermediate bottom arranged inside the space enclosed by the basin at a vertical distance from the basin edge, wherein underneath the intermediate bottom there is arranged a first

branch of an air supply system connected to a controllable blower which is provided with air outlet openings distributed uniformly over the base surface, which are directed laterally and/or downwards,

~~The device according to claim 59,~~ wherein lifting elements for the intermediate floor which ~~can be moved~~ are movable synchronously vertically up and down by a central drive device are arranged in the substantially rectangular basin in plan view, in the four corners.

70. (currently amended) A device for cleaning dogs comprising a basin having a bottom and a side wall extending upwards from this bottom and comprising a perforated intermediate bottom arranged inside the space enclosed by the basin at a vertical distance from the basin edge, wherein underneath the intermediate bottom there is arranged a first branch of an air supply system connected to a controllable blower which is provided with air outlet openings distributed uniformly over the base surface, which are directed laterally and/or downwards,

~~The device according to claim 59,~~ wherein the intermediate bottom with the part of the air supply system having the air outlet openings associated ~~with it~~ therewith and ~~possibly~~ optionally with a lifting device used for its vertical motion is arranged as a removable unit in the basin.